

# METRALINE EXM25

## Multimeter for Use in Potentially Explosive Atmospheres

3-349-728-03  
2/10.16

### Measurement of

- Voltage
- Resistance
- Current
- Frequency
- Approved in accordance with ATEX directive 2014/34/EU for intrinsically safe and not intrinsically safe electric circuits up to 1000 V
- Highest degree of safety due to encapsulated protective resistors in DATA HOLD test probes CAT IV, 1000 V
- Intrinsically save energy units, rechargeable NiMH battery or lithium battery
- Illuminated display

CAT IV



CE



### Application

Thanks to their intrinsically safe design and rugged antistatic housing with protection class IP54, the instruments are particularly suited for use in mining and chemical/petrochemical industries.

### Features

#### Storage of measured values

The indicated measured value can be „frozen“ on the LC display by pressing the **HOLD** key.

#### Self-test and battery level indicator

The self-test provides for the checking of all display elements and instrument functions. An automatic signal is generated when battery replacement is necessary.

#### Rugged housing

The impact-resistant and dust-proof plastic housing makes the instrument almost indestructible. The display panel is protected by a break-proof cover. Due to its high degree of protection (IP 54), the instrument can also be used in moist atmospheres.

#### High level of safety

Series resistors inserted in the two DATA-HOLD test probes provide for a high level of electrical safety.

### Applicable Regulations and Standards

IEC 61010-1/-31 DIN EN 61010-1/-31 VDE 0411-1/-31	Safety requirements for electrical equipment for measurement, control and laboratory use – Part 1: General requirements – Part 31: Safety requirements for hand-held accessories for testing and measuring
DIN EN 60529 VDE 0470-1	Test instruments and test procedures – degrees of protection provided by enclosures (IP code)
DIN EN 61326-1 VDE 0843-20-1	Electrical equipment for measurement, control and laboratory use – EMC requirements – Part 1: General requirements
IEC / DIN EN 60079-0/-11 VDE 0170-1/-7 ATEX	Explosive atmospheres –Part 0: Equipment – General requirements –Part 11: Intrinsic safety circuit „i“

# METRALINE EXM25

## Multimeter for Use in Potentially Explosive Atmospheres

### Characteristic Values

Measuring functions with automatic measuring range selection	Resolution	Limit deviation at +10 ... 30 °C
<b>AC and DC Voltage</b>		
AC 10, 100, 1000 V (1160 V), TRMS	0.01 ... 1 V	
0 ... 100 Hz		±(1,5% + 3 digits)
101 ... 500 Hz		±(5% + 5 digits)
DC 1, 10, 100, 1000 V (1610 V)	0.001 ... 1 V	±(1,5% + 3 digits)
<b>Continuity/Resistance</b>		
200 Ω, 2000 Ω		
20 kΩ, 200 kΩ, 2000 kΩ, 2 MΩ, 20 MΩ	0.1 ... 10 kΩ	±(1% + 5 digits)
<b>Current</b>		
AC/DC 1000 mA, 2 A	1 ... 10 mA	±(1% + 2 digits)
<b>Frequency</b>		
200, 2000 Hz	0.1 ... 1 Hz	±(1% + 2 digits)
10 kHz	0.01 kHz	3% + 2 digits

### Nominal voltage ranges

can be used in electrical systems for categories  
Ex I up to 1000 V, Ex IIB and Ex IIC up to 690 V

### Input resistance

2 MΩ spread over 4 resistors,  
firmly encapsulated in the DATA-HOLD test probes


### Digit display


Type LCD, 7 segment digits,  
2 lines with background illumination  
Display range 0 ... 1999 counts, 3½ digits  
Overflow display „OL“ is indicated

LEDs one each for voltage and resistance

### EG Prototype Test Certificate

BVS 13 ATEX E 089

 II 2G Ex ib IIC T4/T6 Gb  
(Petrochemical industry)

 I M2 Ex ib I Mb  
(Coal mines)

### Electrical Safety

**CAT IV 1000 V**  
with Data-Hold test probes

### Intrinsically safe electric circuits

Current (up to 50 V peak) 2 A  
internal inductivity  $L_i < 5 \mu\text{H}$   
Testing for absence of voltage with Data-Hold test probes 1 kV:  
Category IIC AC/DC  $\leq 690 \text{ V}$   
Category IIB AC/DC  $\leq 690 \text{ V}$   
Category I AC/DC  $\leq 1000 \text{ V}$

### Resistance ranges – maximum values in the event of defect

Voltage 6 V  
Current 2 mA

### Maximum permissible external capacitance/inductivity

Category IIC 40  $\mu\text{F}$ /1000 mH  
Category IIB 1000  $\mu\text{F}$ /1000 mH  
Category I 3000  $\mu\text{F}$ /1000 mH  
Frequency 2 up to 10 kHz

### Power supply

The (rechargeable) batteries specified below may also be replaced in potentially explosive atmospheres as they are of encapsulated, intrinsically safe design.

### Rechargeable NiMH battery

Type EXM-AK9  
Nominal voltage DC 8.4 V  
Maximum voltage U<sub>0</sub> 11.2 V  
Capacity 8.8 Wh  
Temperature class T4

### Lithium battery

Type EXM-LB3  
Nominal voltage DC 3.6 V  
Maximum voltage U<sub>0</sub> 3.9 V  
Temperature class T6

### Electromagnetic Compatibility (EMC)

Interference emission EN 61236-1:2006 class B  
Interference immunity EN 61236-1:2006

### Ambient Conditions

Operating temperatures  $-10 \dots +40 \text{ °C}$   
Relative humidity max. 85%  
Elevation max. 2000 m

### Mechanical Design

Protection type IP54  
Housing impact-resistant, antistatic plastic housing  
( $R < 10^9 \Omega$ ) with unbreakable display cover  
Dimensions 85 mm × 180 mm × 38 mm  
Weight approx. 350 g  
(including (rechargeable) battery)  
Connections – standard jacks for measuring cables  
with standard test probes for Ω/A  
– universal jack with bayonet lock for  
1 kV Data-Hold test probes

# METRALINE EXM25 Multimeter for Use in Potentially Explosive Atmospheres

## Standard Equipment of METRALINE EXM25A

- 1 METRALINE EXM25A multimeter
- 1 set of Data-Hold test probes for V, 1000 V CAT IV
- 1 set of standard test probes for  $\Omega$ /A, 1000 V CAT II 16 A
- 1 Rechargeable NiMH battery
- 1 plug-in power supply unit NG4
- 1 set of operating instructions

## Standard Equipment of METRALINE EXM25B

- 1 METRALINE EXM25B multimeter
- 1 set of Data-Hold test probes for V, 1000 V CAT IV
- 1 set of standard test probes for  $\Omega$ /A, 1000 V CAT II 16 A
- 1 Lithium battery
- 1 set of operating instructions

## Order Information

Description	Type	Article Number
Multimeter with rechargeable NiMH battery	METRALINE EXM25A	M210A
Multimeter with lithium battery	METRALINE EXM25B	M210B
Ever-ready leather case with carrying strap	EXM-LED Leather case	Z209L
Intrinsically safe rechargeable NiMH battery, 9 V (T4) 40 h, for screwing into the multimeter	EXM-AK9 NiMH rechargeable battery	Z209A
Intrinsically safe lithium battery, 3.6 V (T6), 300 h, encapsulated, for screwing into the multimeter	EXM-LB3 lithium battery	Z209B
Plug-in power supply unit for charging rechargeable NiMH battery EXM-AK9	NG4	Z209P

## Accessories

Ever-ready leather case EXM-LED (Z209L)



Intrinsically safe rechargeable NiMH battery EXM-AK9 (Z209A)



Intrinsically safe lithium battery EXM-LB3 (Z209B)



Plug-in power supply unit NG4 (Z209P)



# **METRALINE EXM25**

## **Multimeter for Use in Potentially Explosive Atmospheres**

---

---

Edited in Germany • Subject to change without notice • A pdf version is available on the Internet



GMC-I Messtechnik GmbH  
Südwestpark 15  
90449 Nürnberg • Germany

Phone +49 911 8602-111  
Fax +49 911 8602-777  
E-Mail [info@gossenmetrawatt.com](mailto:info@gossenmetrawatt.com)  
[www.gossenmetrawatt.com](http://www.gossenmetrawatt.com)