


HTE Series

with polyamide insulating body

- UL94V-0
- mounting onto PR/3 type rails according to IEC 60715 Std., "TH/35" type
- for earth connection with yellow/green insulating body



yellow/green version

TECHNICAL CHARACTERISTICS	
----------------------------------	--

function / type	
rated cross-section	(mm ²)
connecting capacity	
flexible	(mm ²)
rigid	(mm ²)
max. flexible with ferrule (mm ²)-ferrule type	
rated voltage / rated current / gauge	conf. to IEC 60947-7-1
rated voltage / rated current / AWG	UL
rated impulse withstand voltage / pollution degree	
insulation stripping length	(mm)
height / width / thickness	TH/35 7,5 mm
height / width / thickness	TH/35 15 mm
height / width / thickness	G32

APPROVALS

ACCESSORIES

End sections	grey blue
Permanent cross connection	
Rated current carrying capacity of jumper	(A)
Cross-connection identification strip (100 mm)	green
Multiple common bar	250 mm
Shunting screw and sleeve	
Coloured partition	red, green, white
Cross connection barrier	red
Test plug socket	
Test plug	
Modular test plug	
End section for modular test plug	
Numbering strip	
Screwdriver for the activation of the spring	
Warning plate	on adjacent terminal blocks
Marking tag	printed or blank
End bracket	
Mounting rail according to IEC 60715 Std.	

HTE.4

Cat. No. **HT250**

TECHNICAL CHARACTERISTICS	
----------------------------------	--

earth	4
earth	4
0,2 ÷ 6	
0,2 ÷ 6	
4 - WP40/16	
- / - / A4	
- / - / 24-10 AWG	
8 KV / 3	
17	
45 / 58 / 6,2	
52 / 58 / 6,2	
-	



Type

HMT.4/PT/GR Cat. No. **HM251GR**

-	
PTC/5/02 poles	PTC0502
PTC/5/03 poles	PTC0503
PTC/5/05 poles	PTC0505
PTC/5/10 poles	PTC0510
PTC/5/00 (40 poles)	PTC0500
32	
PTC/SP	PTC0990
-	
DFH/1	DH01..
-	
SDD/1	DD001
-	
CNU/8/61	NU0861
CCH/2,5-4	CCH02
-	

CNU/8/61	NU0861
BTU for PR/DIN and PR/3	BT005
BTO	BT007
BT/3 for PR/3 only	BT003
-	
PR/3/AC of steel	PR003
PR/3/AS same with slots	PR005

HTE.4/1+2

Cat. No. **HT260**

TECHNICAL CHARACTERISTICS	
----------------------------------	--

earth, 1 input and 2 outputs	4
earth, 1 input and 2 outputs	4
0,2 ÷ 6	
0,2 ÷ 6	
4 - WP40/16	
- / - / A4	
-	
8 KV / 3	
17	
45 / 78 / 6,2	
52 / 78 / 6,2	
-	



Type

HMT.4/1+2/PT/GR Cat. No. **HM211GR**

-	
PTC/5/02 poles	PTC0502
PTC/5/03 poles	PTC0503
PTC/5/05 poles	PTC0505
PTC/5/10 poles	PTC0510
PTC/5/00 (40 poles)	PTC0500
32	
PTC/SP	PTC0990
-	
DFH/1	DH01..
-	
SDD/1	DD001
-	
CNU/8/61	NU0861
CCH/2,5-4	CCH02
-	

CNU/8/61	NU0861
BTU for PR/DIN and PR/3	BT005
BTO	BT007
BT/3 for PR/3 only	BT003
-	
PR/3/AC of steel	PR003
PR/3/AS same with slots	PR005

HTE.4/2+2

Cat. No. **HT270**

TECHNICAL CHARACTERISTICS	
----------------------------------	--

earth, 2 inputs and 2 outputs	4
earth, 2 inputs and 2 outputs	4
0,2 ÷ 6	
0,2 ÷ 6	
4 - WP40/16	
- / - / A4	
-	
8 KV / 3	
17	
45 / 98 / 6,2	
52 / 98 / 6,2	
-	



Type

HMT.4/2+2/PT/GR Cat. No. **HM221GR**

-	
PTC/5/02 poles	PTC0502
PTC/5/03 poles	PTC0503
PTC/5/05 poles	PTC0505
PTC/5/10 poles	PTC0510
PTC/5/00 (40 poles)	PTC0500
32	
PTC/SP	PTC0990
-	
DFH/1	DH01..
-	
SDD/1	DD001
-	
CNU/8/61	NU0861
CCH/2,5-4	CCH02
-	

CNU/8/61	NU0861
BTU for PR/DIN and PR/3	BT005
BTO	BT007
BT/3 for PR/3 only	BT003
-	
PR/3/AC of steel	PR003
PR/3/AS same with slots	PR005