

LED PILOT LIGHT Ø22





DESCRIPTION	POWER SUPPLY	CODE	WEIGHT gramm	MIN. PACK QUANTITY	SIZES
SINGLE LED INDICATOR X1 ⊗ X2	AC/DC 6V I	PLML I L6	15	10	
	AC/DC 12V I	PLML I L12	15	10	
	AC/DC 24V	PLML I L24	15	10	
	AC/DC 48V	PLML I L48	15	10	
	AC/DC 110V	PLML I L110	15	10	
	AC/DC 220V	PLML I L220	15	10	
	AC 380V I	PLML I L380	15	10	

COMPLY WITH RULES

EN60947-5-1 / GB 14048.5

DIAGRAM

Operational temperature	°C	-5 +40
Operational umidity		45% ... 90%
AC rated frequency	Hz	50/60
Rated insulation voltage	1 min V	2500V
Over voltage category	EN60947.1	III
Pollution grade	EN60947.1	3
Protection degree	EN60529	IP65, IP2X terminals
Connection:		
Terminal block caliber		A2
Terminal screw		M3,5
Flexible and solid conductor section	min/max	n. 1 1/2,5 mm ² - n. 2 1/2,5 mm ²
Rated operational voltage Ue	AC/DC V	6, 12, 24, 48, 110, 220
	AC V	380
Rated operational voltage Ie	mA	≤80 6,12V
	mA	≤20 24, 48, 110, 220, 380V
Electrical life	h	≥30.000
Brightness	cd/m ²	100
Mounting	mm	Ø22,5



MULTIFUNCTION PUSH BUTTONS Ø22 | NOT LIGHT



TYPE	COLOUR INDEX	CODE	WEIGHT grams	MIN. PACK QUANTITY	SIZES
DUAL PUSH BUTTON		PPDN	38	10	



TYPE	COLOUR INDEX	CODE	WEIGHT grams	MIN. PACK QUANTITY	SIZES
EXTENDED DUAL PUSH BUTTON		PPDNR	38	10	
		PPDNR.3	38	10	



TYPE	COLOUR INDEX	CODE	WEIGHT grams	MIN. PACK QUANTITY	SIZES
MULTIFUNCTION PUSH BUTTON		PPMN	40	10	

MULTIFUNCTION PUSH BUTTONS Ø22 | LIGHT



TYPE	COLOUR INDEX	CODE	WEIGHT grams	MIN. PACK QUANTITY	SIZES
DUAL PUSH BUTTON		PPDL	30	10	
		PPDL.1	30	10	



TYPE	COLOUR INDEX	CODE	WEIGHT grams	MIN. PACK QUANTITY	SIZES
EXTENDED DUAL PUSH BUTTON		PPDLR	30	10	
		PPDLR.3	30	10	